



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G11B 7/013, 7/00, 20/12, 27/19, 27/30		A1	(11) International Publication Number: WO 98/15951
			(43) International Publication Date: 16 April 1998 (16.04.98)
(21) International Application Number: PCT/JP97/03559			(81) Designated States: CN, ID, JP, KR, MX, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(22) International Filing Date: 6 October 1997 (06.10.97)			
(30) Priority Data: 8/265876 7 October 1996 (07.10.96) JP 8/269580 11 October 1996 (11.10.96) JP			
(71) Applicant: MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571 (JP).			
(72) Inventors: ISHIDA, Takashi; 13-14, Hashimotoisoku, Yawata-shi, Kyoto 614 (JP). KUBOTA, Shinji; 5-16-30, Terakawa, Daito-shi, Osaka 574 (JP). SHOJI, Mamoru; 3-13-4-805, Mozuumemachi, Sakai-shi, Osaka 591 (JP). ISHIDA, Shinji; 4-3-2-204, Matsugaoka, Akashi-shi, Hyogo 673 (JP).			
(74) Agents: TAKIMOTO, Tomoyuki et al.; Matsushita Electric Industrial Co., Ltd., 1006, Oaza Kadoma, Kadoma-shi, Osaka 571 (JP).			

(54) Title: OPTICAL DISC, OPTICAL DISC DEVICE, AND METHOD FOR RECORDING AN OPTICAL DISC

(57) Abstract

In an optical disc, a sector is sequentially formed with a first gap field, a first guard data recording field, a data recording field composed of synchronous signal and user data, a second guard data recording field, and a second gap field, wherein the length of the first and second gap fields, and the length of the first and second guard data recording fields is changed randomly in every recording, and the changing amount of the first and second gap fields is set smaller than the changing amount of the first and second guard data recording fields, thereby suppressing optical disc medium deterioration in every sector and every mark resulting from repeated recording.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

OPTICAL DISC, OPTICAL DISC DEVICE, AND METHOD FOR RECORDING AN OPTICAL DISC

FIELD OF THE INVENTION

The present invention relates to an optical disc for recording and reproducing digital signals in a sector unit of an optical disc, an optical disc device, and a recording method for an optical disc.

DESCRIPTION OF THE PRIOR ART

Optical discs are presently widely distributed as read-only recording media for audio and video use, e.g., a compact disc (CD), and as rewritable recording media, e.g., a mini disc (MD). Moreover, as an external memory device for a computer, rewritable 3.5-inch magneto-optical discs and 5-inch phase change optical discs (PD) are becoming popular.

Henceforth, as the recording media for multimedia, digital video disc (DVD) using phase change optical discs is about to be popularly marketed. One of the merits of the phase change optical disc is that to overwrite an information signal, only a single laser beam is necessary as a recording means. That is, when a modulated laser output is emitted onto a recorded information track as a function of an information signal switching between a recording level and an erasing level, a new signal can be recorded while erasing an existing information signal.

A format structure of such an optical disc is explained by referring to Fig. 18. In Fig. 18, reference numeral 1 is an optical disc, 2 represents tracks on the optical disc 1, and 3 designates sectors dividing the tracks into plural fields. Each sector 3 is composed of a header field 4 including track and sector address information, a gap field 7 with no signal recorded therein, a data recording field 5 for recording user data, and a buffer field 6 for absorbing the effects of imprecision in rotation of the motor.

The header field 4 is usually formed of prepits, and is not used for recording. Reference numeral 4a is a synchronous signal VFO for synchronizing, 4b is an address mark for detecting the header field by a special recording pattern not appearing on the modulation pattern, 4c is a field containing a physical

identification address (PID) having address information with respect to a physical position of the sector, and 4d is an ID error detection (IED) for detecting an address error. The header field composed of blocks 4a to 4d may be composed of plural header fields in order to enhance the reliability thereof.

5 The data recording field 5 is composed of a synchronous signal VFO 5b for synchronizing and user data 5c.

10 Referring now to Fig. 19, an optical disc device for recording and reproducing signals by a recordable optical disc is explained. In Fig. 19, reference numeral 1 is an optical disc, 10 is an optical head for recording and reproducing signals on tracks of the optical disc 1, 11 is a servo control circuit for focusing an optical beam of a semiconductor laser on the tracks of the optical disc, 12 is a laser driving circuit for controlling the optical output of the semiconductor laser, 13 is a data modulation circuit for digitally modulating coded data into a form suited to recording, and 14 is a VFO generating circuit for generating VFO as a synchronous signal. Reference numeral 15 is a coding circuit for performing error correction coding on recorded data, 16 is a record control circuit for controlling the timing of recording, 17 is an address detecting circuit for detecting an address signal from a reproduced signal, 18 is a system control circuit for controlling the operation of the entire optical disc device composed of a microprocessor, and other related circuitry, and 19 is data to be recorded.

20 The data coded in the coding circuit 15 is modulated in the data modulation circuit 13 and is output as modulated data. The synchronous signal VFO generated in the VFO generating circuit 14 is added to the beginning of this modulated data and is delivered to the laser driving circuit 12, and is recorded in the optical disc 1.

25 In such a rewritable light-operative optical disc, however, the number of recording repetitions is limited, since the recording medium deteriorates due to thermal load, under repeated exposure to light. Generally, such deterioration phenomena tend to be more prevalent in the deterioration area as the number of recording repetitions increases. Deterioration phenomena may be roughly classified into two types as follows:

30

(1) deterioration phenomenon in each sector, occurring in the beginning end (record start position) of a recording field in the sector and terminating end (record end portion), by repeated recording on the sector, and

(2) deterioration phenomenon in each mark, occurring in the mark area, as the mark row of a same pattern is recorded repeatedly in the same position in the sector.

First, in the deterioration phenomenon in each sector, as recording is repeated, deterioration gradually occurs in the recording foil in the beginning end and terminating end of a recording field in the sector, and this defect expands backward of the sector from the beginning end (to the relative laser advancing direction on the optical disc) and forward of the sector from the terminating end (to the reverse direction of the relative laser advancing direction on the optical disc).

The above-described phenomenon is understood to occur because, when the recording foil is in a fused state, a movement phenomenon of the recording foil substance in the track direction occurs. For instance, by the movement of the recording foil substance to the sector forward direction, as fusion and solidification are repeated multiple times, the recording foil substance accumulates in the record start point portion where the thermal load to the recording foil changes suddenly, and the recording foil substance is decreased in thickness at the recording end point portion. As a result, the film thickness becomes uneven between the recording start point and end point, and thermal or optical characteristics deteriorate, the film exfoliates, and/or the quality of reproduced signals deteriorates in the data beginning end or terminating end, thereby impeding correct recording and reproducing of information.

Next, in the deterioration phenomenon in each mark, as the recording is repeated, a defect occurs in the recording foil when recording the same pattern, and this defect expands forward and backward of the mark portion.

That is, when the same data is repeatedly recorded in the same sector, fusion and solidification are repeated multiple times in some areas, while other areas are not fused at all.

Generally, when rewriting the recorded data in an optical disc, the data is rewritten in the sector unit. Therefore, if information is changed in part of a sector, the entire sector is rewritten. In a TOC (Table of Contents) field or a directory field where information corresponding to the table of contents of the recorded information in the disc is recorded, in particular, similar data are often recorded repeatedly, and the rewriting frequency is high. In the ordinary data sector, too, same data is recorded repeatedly in the synchronous signal portion VFO or the like, and the aforementioned kind of deterioration phenomenon occurs in such instances. As a result, the film thickness of the recorded film fluctuates in the boundary region of the portion fused and solidified repeatedly and the portion not fused at all, and thus the thermal and optical characteristics deteriorate, and the quality of reproduced signal in this portion deteriorates, thereby blocking normal recording and reproducing of information.

OBJECT AND SUMMARY OF THE INVENTION

The present invention is directed, in the light of the above described problems, to an optical disc for recording and reproducing data in the unit of sectors. It is an object of the invention to provide an optical disc capable of reducing the deterioration of the recording foil of the optical disc in every sector and every mark derived from repeated recording, simplifying the associated signal processing system, and suppressing effects of deterioration phenomena on accurate recording and reproducing of information, and an optical disc device, and a recording method for an optical disc.

To achieve these and other objects, in a first feature of the optical disc of the invention, a header field including a sector identifying signal, and a data recording field including a synchronous signal are provided in each one of plural sectors dividing the tracks, and a guard data recording field for recording specific guard data is provided between the header field and data recording field.

With this guard data recording field, the synchronous signal can be protected from deterioration of the medium due to repeated recording.

In a second feature of the optical disc of the invention, the guard data in the guard data recording field is the same as the recording pattern in the synchronous signal field, and the phase of the recording pattern is continuous near the boundary of the guard data recording field and synchronous signal field.

5 As a result, the guard data recording field can be substantially utilized as the synchronization signal field, and the lock-in range of synchronization can be expanded further than the synchronous signal field, so that the stability of acquisition of synchronism can be improved even in view of medium deterioration due to repeated recording.

10 In a third feature of the optical disc of the invention, the recording section of the guard data recording field is changed randomly in every recording.

As a result, the guard data recording field for recording identical signal patterns and the mark position recorded on the recording medium by repeated recording is shifted randomly in every recording, so that deterioration of the recording medium can be prevented.

15 In a fourth feature of the optical disc of the invention, a sector-structure is formed to comprise, sequentially, a first gap field having no signal, a first guard data recording field for recording guard data, a data recording field including synchronous signal and user data, a second guard data recording field, and a second gap field, wherein the total length of the first and second gap fields is constant, the total length of the first and second guard data recording fields is constant, and, in the sector, at the time of recording, the length of the first gap field and the first guard data recording field is changed randomly upon every recording, and the changing amount of the first gap field is set smaller than the changing amount of the first guard data recording field.

20 Accordingly, since the first and second gap fields and the first and second guard data recording fields change randomly upon every recording, the medium deterioration in every sector and in every mark due to repeated recording can be suppressed.

30 In a fifth feature of the optical disc of the invention, in addition to the fourth feature, the resolution of the changing amount of the first gap field is a channel bit

unit, and the resolution of the changing amount of the first guard data recording region is a byte unit.

Hence, while maintaining the ease of realization of data processing on the signal processing system, the medium deterioration in every sector and in every mark due to repeated recording can be suppressed.

In a sixth feature of the optical disc of the invention, in addition to the fourth feature, the signal polarity of guard data and data recording field data is changed randomly upon every recording.

As a result, even in a limited random shift amount, the medium deterioration in every sector and in every mark can be suppressed.

The optical disc device of the invention comprises means for recording and reproducing the optical discs as mentioned herein, and is capable of suppressing the medium deterioration in every sector or in every mark due to repeated recording.

The recording method for an optical disc of the invention comprises a method of recording these optical discs, and is hence capable of suppressing the medium deterioration in every sector or in every mark due to repeated recording.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram showing a format structure of an optical disc according to a first embodiment of the invention.

Figs. 2a-c show deterioration of the recording medium and synchronous signal field VFO at the record start point when recorded repeatedly.

Fig. 3 is a block diagram of an optical disc device according to a second embodiment of the invention for recording in and reproducing from an optical disc having a guard data recording field.

Figs. 4a-d depict a synchronous signal section in which guard data in a guard data recording field has a pattern different from the synchronous signal VFO.

Figs. 5a-d show a synchronous signal section of an optical disc in a third embodiment in which guard data in a guard data recording field has the same pattern as the synchronous signal VFO.

Fig. 6 is a block diagram of an optical disc according to a fourth embodiment for recording and reproducing in which the recording pattern in the guard data recording field is the same as the synchronous signal field VFO.

5 Fig. 7 is a flowchart for explaining a recording method for an optical disc according to a fifth embodiment for recording and reproducing in which the recording pattern in the guard data recording field is the same as the synchronous signal field VFO.

10 Figs. 8a-d depict the conditions of sectors of an optical disc according to a sixth embodiment for changing randomly the sector recording section upon every recording.

Fig. 9 is a block diagram of an optical disc device according to a seventh embodiment for recording and reproducing a signal in an optical disc by changing randomly the sector recording section upon every recording.

15 Fig. 10 is a format of an optical disc for recording and reproducing by randomly changing the recording section in first and second gap fields and first and second guard data recording fields, in every sector, upon every recording.

20 Fig. 11 is a block diagram of an optical disc device according to an eighth embodiment for recording and reproducing by changing randomly the recording section in first and second gap fields and first and second guard data recording fields, in every sector, upon every recording.

Fig. 12 is a block diagram showing an example of a second random changing circuit.

Fig. 13 is a flowchart for explaining a recording method of the optical disc according to the eighth embodiment.

25 Figs. 14a-d depict the mode of the sector when randomly changing the first and second gap fields and first and second guard data recording fields.

Figs. 15a-b show the deterioration area of the sector when randomly changing the first and second gap fields and first and second guard data recording fields.

30 Figs. 16a-c are diagrams for explaining the polarity of recording signal and the recording stage on an actual optical disc.

Fig. 17 is a graph of results of an experiment showing the effect of random shift according to the invention.

Fig. 18 is a format of a conventional recordable optical disc.

Fig. 19 is a block diagram of a conventional recordable optical disc device.

5 DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, embodiments of the invention are described below.

Embodiment 1

Fig. 1 shows a format structure of an optical disc according to a first embodiment of the invention. Explanation is omitted for the parts also shown in the format structure of Fig. 18 relating to the prior art described above.

5 As compared with the prior art, the added and modified portion is a guard data recording field 100 for recording guard data, disposed between the header field 4 and data recording field 5. The guard data recording field 100 is disposed behind the gap field 7 and immediately before the data recording field 5. Since no signal is recorded in the gap field 7, recording of signals in the sector begins at the guard data recording field 100.

Referring to Figs. 2a-c, in the optical disc having the format structure in Fig. 1, the relation between deterioration of the recording medium at the record start point and synchronous signal field VFO upon repeated recording is explained.

15 Figs. 2a-c show the mode of deterioration of the recording medium near the record start point of the data recording field 5, in which Fig. 2a shows a single repetition only, Fig. 2b shows 50,000 repetitions, and Fig. 2c shows 100,000 repetitions.

20 In the initial stage of a single repetition in Fig. 2a, the guard data recording field 100 at the start point of recording of the sector, is free from medium deterioration, and thus there is no problem. Here, the interval of the guard data recording field in the initial state is supposed to be T1, and the interval of the synchronous signal field VFO is supposed to be T2.

25 After 50,000 repetitions as shown in Fig. 2b, medium deterioration occurs and is indicated by 30 for an interval of TC1 at the beginning of the guard data recording field 100., the guard data recording field 100 shortens to T4 by the interval TC1 of the length of the medium deterioration 30. However, if medium deterioration occurs, only the guard data recording field 100 in which guard data is recorded is shortened in length. The synchronous signal field VFO necessary for synchronization is completely free from the effects of medium deterioration 30, and the synchronous interval T2 remains the same as in the initial state. Hence, as in the
30 initial state, stable acquisition of synchronism is realized.

After 100,000 repetitions as shown in Fig. 2c, the medium deterioration 30 at the beginning of the guard data recording field 100 is extended to interval TC2. As a result, the guard data recording field 100 shortens further to be T5. However, only the guard data recording field in which guard data is recorded is shortened in length, and the synchronous signal field VFO necessary for synchronization is completely free from the effects of the medium deterioration 30, and the synchronous interval T2 likewise remains the same as in the initial state. Hence, as in the initial state, stable acquisition of synchronism is realized.

As explained, according to the present embodiment, by providing the guard data recording field 100 for recording guard data between the header field and the data recording field containing synchronous signal, the synchronous signal field is prevented from being shortened by the medium deterioration caused by repeated recording, so that the acquisition of synchronism is stabilized.

Embodiment 2

Referring now to Fig. 3, an optical disc device according to a second embodiment of the invention which is intended to record and reproduce in an optical disc having a guard data recording field at the beginning of a sector is described. Explanation is omitted for the parts already discussed in the optical disc device of Fig. 18 relating to the prior art described above.

What is added to the prior art is a guard data generating circuit 200 and a first record control circuit 201. The guard data generating circuit 200 generates specified guard data. The guard data of the guard data generating circuit 200 is first provided, synchronous signal VFO of the synchronous signal VFO generating circuit 14 is added next, and then modulated data of the data modulating circuit 13 is added later still. Such data timing is controlled by the first record control circuit 201. The combined guard data, synchronous signal VFO, and modulated data are provided to the laser driving circuit 12, and is recorded on the optical disc.

According to the present embodiment, as described herein, in addition to the conventional constitution of the optical disc device, the guard data generating circuit 200 for generating guard data and first record control device 201 are

provided, and by recording the guard data in the guard data recording field 100 between the header field 4 and the synchronous signal field VFO at the starting portion of the data recording field 5, the synchronous signal is protected from medium deterioration caused by repeated recording, so that an optical disc device stable in acquisition of synchronism is realized.

Embodiment 3

Figs. 4a-d and Figs. 5a-d show the relationship between the deterioration of recording medium at the record start point upon repeated recording and the synchronizing interval of synchronous signal field VFO, in an optical disc having a format structure according to a third embodiment of the present invention. In the optical disc of the third embodiment, the recording pattern of guard data in the guard data recording field is the same as the recording pattern of the synchronous signal field VFO. In the boundary of the guard data recording field and synchronous signal field, moreover, the phase of the recording pattern is matched so as not to cause discontinuation.

First, in Figs. 4a-d, the guard data in the guard data recording field is different from the recording pattern of the synchronous signal field VFO. Fig. 4a shows the data recording field after one repetition, Fig. 4b shows the lock-in range on synchronization, Fig. 4c shows the data recording field after 100,000 times of repetition, and Fig. 4d shows the lock-in range on synchronization after 100,000 times of repetition.

In the initial state after one repetition, the guard data recording field 100 at the record start point of the data recording field 5 is free from medium deterioration. The interval of the guard data recording field in the initial state is supposed to be T1, and the interval of the synchronous signal field VFO is supposed to be T2.

The lock-in range on synchronization 300 after one repetition is the interval T2 of the synchronous signal field VFO.

In the case after 100,000 times of repetition shown in Fig. 4c, at the beginning of the guard data recording region 100, medium deterioration 30 occurs for an interval of TC2. Accordingly, the guard data recording field 100 is shortened to an

interval T5. However, only the guard data recording field in which guard data is recorded is shortened, and the synchronous signal field VFO necessary for synchronization is not influenced at all by the medium deterioration 30.

5 The lock-in range on synchronization 300 after 100,000 times as shown in Fig. 4d remains at T2 as in the initial state after one repetition. Hence, as in the initial state, a stable acquisition of synchronism is realized.

10 In Figs. 5a-d, the guard data in the guard data recording field is the same as the recording pattern of the synchronous signal field VFO. Moreover, so as not to be discontinuous at the boundary of the guard data recording field and synchronous signal field, the phase of the recording pattern is matched. Fig. 5a shows the data recording field after one repetition, Fig. 5b shows the lock-in range on synchronization, Fig. 5c shows the data recording field after 100,000 times of repetition, and Fig. 5d shows the lock-in range on synchronization after 100,000 times of repetition.

15 In the initial state after one repetition as shown in Fig. 5a, the guard data recording field 100 at the record start point of the data recording field 5 is free from medium deterioration. The interval of the guard data recording field in the initial state is supposed to be T1, and the interval of the synchronous signal field VFO is supposed to be T2.

20 The lock-in range on synchronization 400 after one time of repetition is thus the sum $T1+T2$ of interval T1 of the guard data recording field and interval T2 of the synchronous signal field VFO because the signal in the guard data recording field is the same recording pattern as in the synchronous signal field VFO and continuity is maintained. As compared with T2 of the lock-in range on synchronization 300 in the recording pattern in which the signal of the guard data recording field is different from the synchronous signal field VFO explained in Figs. 4a-d, the lock-in range in the present embodiment is extended by the portion of the interval T1 of the guard data recording field.

25 In the case after 100,000 times of repetition shown in Fig. 5c, at the beginning of the guard data recording region 100, medium deterioration 30 occurs for an interval of TC2. Accordingly, the guard data recording field 100 is shortened to an

interval T5. However, only the guard data recording field in which guard data is recorded is shortened, and the synchronous signal field VFO necessary for synchronization is not at all influenced by the medium deterioration 30.

5 The lock-in range on synchronization 400 after 100,000 times of repetition shown in Fig. 5d is the sum T5+T2 of interval T5 of the guard data recording field 100 and interval T2 of the synchronous signal field VFO. As compared with T2 of the lock-in range on synchronization 300 in the recording pattern in which the signal of the guard data recording field is different from the synchronous signal field VFO explained in Figs. 4a-d, the lock-in range is extended by the portion of the interval of
10 the guard data recording field.

Accordingly, even if after 100,000 recording repetitions causing medium deterioration at the record start point, the lock-in range on synchronization is longer than the interval T2 of the initial synchronous signal field VFO by the portion of the interval T5 of the guard data recording field. As a result, stability and reliability of
15 (phase locked loop (PLL) synchronization are improved.

As described herein, according to the present embodiment, by providing guard data in the guard data recording field 100 disposed between the header field 4 and data recording field of the optical disc, with the same recording pattern as in the synchronous signal field VFO, and keeping continuity, the lock-in range on
20 synchronization can be extended beyond the synchronous signal field VFO, and, therefore, if medium deterioration due to repeated recording occurs, the stability and reliability of acquisition of synchronism can still be maintained.

Embodiment 4

25 Referring now to Fig. 6, an optical disc device according to a fourth embodiment of the invention is described, which embodiment is intended to record and reproduce by providing the recording pattern guard data recording field at the beginning of a sector, the guard data being the same as in the synchronous signal field VFO. Explanation is omitted for the parts already described in the optical disc device in Fig. 19 relating to the prior art described above.

What is added to the prior art is a VFO guard data generating circuit 500 and a first record control circuit 201. The VFO guard data generating circuit 500 generates the same recording pattern in the guard data recording field 100 and synchronous signal field VFO. The first record control circuit 201 generates continuous gate timing so as not to cause any discontinuity between the guard data recording field 100 and synchronous signal field 5b. As a result, in the guard data recording field 100 and synchronous signal field 5b, the same recording patterns for synchronization are generated continuously.

To the beginning of the recording pattern generated in the VFO guard data generating circuit 500, modulated data from the data modulation circuit 13 is added. Such data timing is controlled by the first record control circuit 201. The combined data is provided to a laser driving circuit 12 in a later stage, and is recorded on the optical disc.

According to the present embodiment, as described herein, by adding the VFO guard data generating circuit 500 for generating common recording patterns in the guard data recording field 100 and synchronous signal field VFO and the first record control circuit 201 to the conventional optical disc device, the recording pattern for synchronization is recorded in the guard data recording region 100 between the header field 4 and synchronous signal field VFO, and, therefore, the lock-in range on synchronization is extended beyond the interval of the synchronous signal field VFO, so that an optical disc device enhanced in reliability and stabilization of acquisition of synchronism even in view of medium deterioration occurring due to repeated recording can be realized.

Embodiment 5

Fig. 7 is a step-by-step explanation of a recording method for an optical disc according to a fifth embodiment of the present invention for recording and reproducing the same recording pattern in the synchronous signal field VFO in the guard data recording field at the beginning of a sector.

At step 210, the optical disc device reads the address information of the optical disc by a command from a host system in an address detecting circuit 17 (see Fig. 6, for example). A system control circuit 18 confirms whether an address of the sector is to be recorded or not.

At step 211, the record data is coded in a coding circuit 15, and is modulated in a data modulation circuit 13 that outputs modulated data.

At step 212, to the beginning of the modulated data, a synchronous signal VFO for synchronization is added by a VFO generating circuit 14.

At step 213, to the beginning of the synchronous signal VFO, guard data for suppressing the effects of medium deterioration is added by a guard data generating circuit 200.

Then, at step 214, in the corresponding sector to be recorded, the record data generated at steps 211, 212, and 213 are controlled by the first record control circuit 201 and recorded in the proper order. Specifically, the guard data is recorded in the guard data recording field, and the synchronous signal VFO and user data are recorded in the data recording field.

With these steps, the data can be recorded and reproduced in the optical disc in the recording format shown in Fig. 1.

Embodiment 6

Referring now to Figs. 8a-d, an optical disc according to a sixth embodiment of the invention is described below, in which the recording interval of the guard recording field is changed at random in every recording.

In Figs. 8a-d, the variable recording intervals of the guard data recording field 100 in sectors 1, 2, 3, and 4, respectively, are shown.

In Fig. 8a, relating to sector 1, the recording interval of the guard data recording field 100 is T_1 , and the interval of the succeeding synchronous signal field VFO is T_2 . The combined interval of the guard data recording field 100 and synchronous signal field VFO is T_1+T_2 .

5 In Fig. 8b, relating to sector 2 next to sector 1, the recording interval of the guard data recording field 100 is extended by interval dT compared to sector 1 to be T_1+dT . The combined interval of the guard data recording field 100 and synchronous signal field VFO is T_1+T_2+dT . It is understood that since the guard data recording field 100 is extended by dT , the terminal end of the data recording field is shifted backward by the same amount.

10 In Fig. 8c, relating to sector 3 next to sector 2, the recording interval of the guard data recording field 100 is extended by interval $2dT$ compared to sector 1 to be T_1+2dT . The combined interval of the guard data recording field 100 and synchronous signal field VFO is thus T_1+T_2+2dT . As the guard data recording field 100 is extended by $2dT$, the terminal end of the data recording field is likewise shifted backward by the same amount.

15 In Fig. 8d, relating to sector 4 next to sector 3, the recording interval of the guard data recording field 100 is T_1 , as in sector 1. The combined interval of the guard data recording field 100 and synchronous signal field VFO is thus again T_1+T_2 .

20 According to this scheme, in every recording, the recording interval in the guard data recording field 100 is randomly changed in every sector at a time resolution of dT . The number of bits for randomly changing this time resolution dT is determined appropriately by the system configuration. A specific example with respect to a phase change optical disc is given below.

25 When the channel bit frequency is 29.18 MHz, for the period $t = 34.27$ nsec of one bit of the channel bit, supposing one byte of data corresponds to 16 channel bits, $16t = 548$ nsec is defined to be one byte in the data. The line velocity is about 6 m/s. The guard data recording field 100 of interval $T_1 = 20$ bytes changes by 20 bytes + K ($K = 0$ to 7), in eight types of 0 to 7 bytes, at a resolution in the unit of one byte. By such random time shift, since the start point of the synchronous signal field VFO can

be changed at random, recording deterioration resulting from the same recording pattern can be prevented. The recording interval of the guard data recording field is $20 \text{ bytes} * 6 \text{ m/s} * 548 \text{ nsec} = 66 \mu\text{m}$.

Although not shown in Figs. 8a-d, the random time shift is preferably also given to the guard data recording field 100 in which the recording pattern is the same as in the synchronous signal field VFO. Accordingly, the length of gap field 7 is changed randomly in every recording. For instance, the gap field interval of 10 bytes ($34 \mu\text{m}$) is changed in 16 ways corresponding to 0 to 15 channel bits, at the resolution in the unit of one channel bit $t = 34.27 \text{ nsec}$. This is described in detail later.

When using such random time shift, according to the relation between the number of times of recording and the deterioration interval in the guard data recording field 100, the deterioration interval is $7 \mu\text{m}$ at 20,000 repeated recordings, $10 \mu\text{m}$ at 50,000 repetitions, and $33 \mu\text{m}$ at 100,000 repetitions.

As a result of employing random time shift, it is found that the deterioration of the recording interval of the guard data recording field 100 is suppressed to $33 \mu\text{m}$ even if recording is repeated 100,000 times. The recording interval of the guard data recording field 100 is set at $66 \mu\text{m}$, and even after 100,000 times of recording, the deterioration of the recording interval is not extended up to the synchronous signal field VFO, so that the acquisition of synchronism remains stable.

Incidentally, since the recording pattern of the guard data recording region is identical to the synchronous signal VFO, the channel bits repeating as 00010001, and alternate repetition of mark and space in the length of four channel bits on the recording medium may be employed.

Embodiment 7

Referring now to Fig. 9, an optical disc device according to a sixth embodiment of the invention is described, which is intended to record and reproduce in an optical disc while randomly changing the recording interval of the guard data recording

field in every recording. Explanation is omitted for the parts already described with respect to the optical disc device in Fig. 19 relating to the prior art described above.

What is added to the prior art is a guard data generating circuit 200, a first record control circuit 201, and a first random changing circuit 220. The guard data generating circuit 200 generates specific guard data. To the beginning of the guard data from the guard data generating circuit 200, a synchronous signal VFO from a synchronous signal VFO generating circuit 14 is added, and then modulated data from a data modulation circuit 13 is added thereafter. The first random changing circuit 220 changes the recording interval of the guard data recording region, by 20 bytes + K (K changing randomly from 0 to 7), at the resolution of 1 byte. While randomly changing the recording interval of the guard data recording field, the timing of the combined guard data, synchronous signal VFO and modulated data is controlled by the first record control circuit 201, and these record signals are provided to a laser driving circuit 12 in a later stage, and recorded in the sectors on the optical disc while changing randomly in every recording.

As described herein, according to the present embodiment, by adding the guard data generating circuit 200 for generating guard data, first record control circuit 201 and first random changing circuit 220 to the conventional optical disc device, the record start point is changed randomly in every recording, and thus signal deterioration due to repeated recording of synchronous signal VFO and user data can be suppressed.

Embodiment 8

Fig. 10 shows a format structure of an optical disc according to an eighth embodiment of the present invention for recording and reproducing by randomly changing the length of first and second gap fields, and first and second guard data recording fields, in every recording, and setting the changing amount of the first gap field smaller than the changing amount of the first guard data recording field. Explanation is omitted for the parts already described in the format structure shown in Fig. 18 relating to the prior art described above.

What is added to the prior art is a mirror field 270 used to adjust a servo signal, a first gap field 271 of no-signal interval, a first guard data recording field 272 for recording guard data, a second guard data recording field 273 for recording guard data next to the data recording field 5, and a second gap field 274 of no-signal interval.

Herein, the recording interval of the first and second gap fields 271, 274, and first and second guard data recording fields 272, 273 is changed randomly in each sector in every recording.

Fig. 11 depicts an optical disc device for recording and reproducing in an optical disc by randomly changing the length of first and second gap fields, and first and second guard data recording fields, in every recording, and setting the changing amount of the first gap field smaller than the changing amount of the first guard data recording field. Explanation is omitted for same parts already described with respect to the optical disc device of Fig. 19 relating to the prior art described above.

What is added to the prior art device is a guard data generating circuit 200, a second record control circuit 230, a second random changing circuit 240, and a polarity inverting circuit 250. The guard data generating circuit 200 generates specific guard data. To the beginning of the guard data from the guard data generating circuit 200, a synchronous signal VFO from a synchronous signal VFO generating circuit 14 is added, and then modulated data from a data modulation circuit 13 is added thereafter. The second random changing circuit 240 changes randomly the recording interval of the first and second gap fields. For example, the first gap field is changed by $10 \text{ bytes} + J/16$ (J changing randomly from 0 to 15) in every recording. Since the resolution of the changing amount is $J/16$, one byte is composed of 16 bits in channel bits. The second gap field is changed by $25 \text{ bytes} - J/16$ (J changing randomly from 0 to 15) in every recording. Accordingly, the total length of the recording interval of the first gap field and the recording interval of the second gap field is kept constant. Moreover, the second random changing circuit 240 also randomly changes the recording intervals of the first and second guard data recording fields. For example, the first guard data recording field is changed by $20 \text{ bytes} + K$ (K changing randomly from 0 to 7, at the resolution of 1 byte. Similarly,

the second guard data recording field is changed by 55 bytes - K (K changing randomly from 0 to 7), at the resolution of 1 byte. Herein, the total length of the recording interval of the first guard data recording field and the recording interval of the second guard data recording field is also kept constant.

5

While randomly changing the recording interval of the first and second gap fields and first and second guard data recording fields, the timing of the combined guard data, synchronous signal VFO, and modulated data is controlled in the second record control circuit 230. The record signal composed of these signals is passed to the polarity inverting circuit 250 in a later stage, and the polarity of the record signal is changed randomly in the sector interval in every recording. The record signal from the polarity inverting circuit 250 is provided to a laser driver circuit 12, and the recording interval of the first and second gap fields and the recording interval of the first and second guard data recording fields are changed randomly, and the polarity of the record signal is changed randomly and is recorded in the sector on the optical disc.

10

15

Referring now to Fig. 12, a structural example of the second random changing circuit 240 is described. In Fig. 12, a random changing circuit 701 is composed of 13 stages of shift registers 702, and is designed to receive a clock 703 and a random update command 704. By the command of the random update command 704, the signal polarity and the changing amount are determined randomly by a one-bit signal 705 for determining the polarity of record signal, a four-bit signal 706 for determining the changing amount of the first and second gap fields, and a three-bit signal 707 for determining the changing amount of the first and second guard data recording fields.

20

25

Fig. 13 is a flowchart showing the operation for rewriting the record information of a sector by this optical disc device.

Referring also to Fig. 11, the operation is described below according to the flowchart in Fig. 13.

At step 261, the optical disc device reads the address information of the optical disc by the command from a host system in an address detecting circuit 17. A

30

system control circuit 18 confirms whether an address of a sector is to be recorded or not.

At step 262, the record data is coded in a coding circuit 15, and is modulated in a data modulation circuit 13 that outputs modulated data.

5 At step 263, to the beginning of the modulated data, a synchronous signal VFO for synchronization is added by a VFO generating circuit 14.

At step 264, to the first guard data recording field at the beginning of the synchronous signal VFO and the second guard data recording field consecutive to the user data, guard data for suppressing the effects of medium deterioration are
10 added by a guard data generating circuit 200.

At step 265, the changing amount of the recording interval of the first and second gap fields is determined randomly by the changing amount of 0 to 15 channel bits, at the resolution of one channel bit. Similarly, the changing amount of the recording interval of the first and second guard data recording fields is determined
15 randomly by the changing amount of 0 to 7 bytes, at the resolution of one byte. That is, by the extended portion of the first gap field, the length of the second gap field becomes shorter, and the total length is unchanged. Similarly, the total length of the first and second guard data recording fields does not vary.

At step 266, while randomly changing the recording interval of the first and second gap fields and first and second guard data recording fields, a record signal is
20 created from the combined guard data, synchronous signal VFO, and modulated data.

At step 267, it is determined whether to invert the polarity of the record signal.

25 At step 268, if determined to invert the polarity at step 267, the polarity of the record signal is inverted.

At step 269, the record signals determined in step 263 through step 268 are recorded in the corresponding sectors to be recorded.

According to the above-described scheme, the signals are recorded in the
30 optical disc in the format as shown in Fig. 10.

The random changing state of the first and second gap fields and first and second guard data recording fields is explained with reference to Figs. 14a-d. Figs. 14a-d depict a recording format in the sector by randomly changing the length of the first and second gap fields and first and second guard data recording fields by the above method. On the sector of optical disc are formed an address signal 401, a first gap field 402, a first guard data recording field 403, a record signal 404 composed of synchronous signal VFO and user data, a second guard data recording field 405, and a second gap field 406.

Fig. 14a shows a case in which the changing amount J of the first gap field 402 is the minimum $J=0$, and the changing amount K of the first guard data recording field 403 is the minimum $K=0$. Therefore, the length of the first gap field 402 is the minimum value of $G1min$, and the length of the second gap field 406 is the maximum value of $G2max$. The length of the first guard data recording field 403 is the minimum value of $D1min$, and the length of the second guard data recording field 405 is the maximum value of $D2max$. In the case shown in Fig. 14a, the record signal 404 is located at the foremost position in the sector.

In Fig. 14b, $J=Jmax$ and $K=0$, in Fig. 14c, $J=0$, $K=Kmax$, and in Fig. 14d, $J=Jmax$, $K=Kmax$. Herein, $Jmax$ is the maximum changing amount of the gap field, which is usually 15 channel bits, and $Kmax$ is the maximum changing amount of the guard field, which is usually 7 bytes. In the case shown in Fig. 14d, the record signal 404 is located at the rearmost position in the sector. The length of the first gap field 402 is the maximum value of $G1max$, and the length of the second gap field 406 is the minimum value of $G2min$. The length of the first guard data recording field 403 is the maximum value of $D1max$, and the length of the second guard data recording field 405 is the minimum value of $D2min$.

Figs. 15a-b show schematic diagrams of deterioration of a sector. In Fig. 15a, $J=0$, $K=0$, and in Fig. 15b, $J=Jmax$, $K=Kmax$. As shown in the diagram, start end deterioration 501 occurs in the first guard data recording field 403, and a start end deterioration region 504 is formed in a total length of the maximum changing amount $Jmax$ portions of the first and second gap fields. Similarly, terminal end deterioration 502 occurs in the second guard data recording field 405, and a

terminal end deterioration region 505 is formed in a total length of the maximum changing amount J_{\max} portions of the first and second gap fields. However, this deterioration region is in the first and second guard data recording fields, and further expansion of the start end and terminal end deterioration regions is prevented, and hence the deterioration region does not detrimentally affect the record signal 404 composed of the synchronous signal VFO and user data.

Incidentally, in the record signal 404 composed of the synchronous signal VFO and user data, since the recording interval is randomly changed and expanded at the resolution of one byte, the range 506 for inducing local oscillation is expanded, and the local deterioration 503 is dispersed, so that the effects of local deterioration may be decreased.

In actual recording operation, J is a channel bit, and one byte is composed of 16 channel bits, and K is a larger value as compared with J . Therefore, the positions of the first and second gap fields change randomly and minutely, while the recording position changes rather widely in the record signal 404 enclosed by the first and second guard data recording fields.

In this embodiment, J is set in channel bit unit, and K in byte unit, to satisfy the following requirements. That is, the random shift of the first and second gap fields is small in scale so as not to expand the deterioration region at the recording start and terminal end, and random shift of channel bit in the minimum unit for handling digital data is realized, whereas local deterioration is dispersed by increasing the changing amount of the recording fields of the synchronous signal and user data record signal, and the arrangement of information is simple.

The first and second guard data recording fields are intended to prevent the deterioration phenomenon occurring at the start and terminal end due to repeated recording from propagating to the record signals such as synchronous signal VFO and user data. Therefore, from the viewpoint of preventing expansion of the deterioration region, the random shift should not be increased too much.

The local deterioration in record signals such as synchronous signal VFO and user data should be preferably dispersed by expanding the inducting region by

changing in byte unit, thereby lowering the possible rate of effects due to deterioration.

Usually, when handling digital data, it is preferred to handle the data in byte units. However, if the random shift is handled in the byte unit alone, deviation occurs in byte unit, and deterioration in byte unit is likely to occur, and therefore as compared with the random shift in channel bit unit, the deterioration preventive effect of the medium is decreased. On the other hand, if random shift is always handled in channel bit unit only a fractional shift of 5 bits or 9 bits occurs, and signal processing is difficult in reproduction.

In this embodiment, accordingly, the random shift in the first and second gap fields in no-signal interval is in channel bit unit, so that deterioration in byte unit can be prevented, and effects of deterioration in byte unit can be prevented, and effects of deterioration at start and terminal end of a sector can be effectively suppressed. In the record signals of synchronous signal VFO and user data, if the random shift is handled in byte unit, the region to be recorded is expanded, and hence deterioration in mark unit can be dispersed, and, moreover, the data to be reproduced can be handled in byte unit, so that no inconvenience is caused in signal processing in reproduction.

As a result, the recording position of record signal 404 of synchronous signal VFO or user data as seen from the entire sector is changed over in two stages of random shift, that is, large random shift and small random shift, in every recording. In the embodiment, for two types of deterioration, that is, deterioration at start and terminal end of a sector and local deterioration occurring in every mark, effects of these deteriorations on recording and reproducing of information can be effectively decreased.

Further according to the present embodiment, the polarity of the record signal is inverted randomly in every recording. Figs. 16a-c shows the relation between the polarity of the record signal and the actual recording state on an optical disc. In the sector of the optical disc are formed an address signal 604, a first gap field 605, a first guard data recording field 601, a record signal 607 composed of

synchronous signal VFO and user data, a second guard data recording field 608, and a second gap field 609.

The record signal 601, if not inverted in polarity, is recorded in the recording medium in a state of 602, and if inverted in polarity, is recorded in the recording medium in a state of 603. That is, by inverting the polarity, the non-fused portion and the fused portion of the foil forming a mark are completely opposite, so that a further effect is added to prevention of deterioration.

Fig. 17 is a diagram showing the result of an experiment confirming the effect of random shift of the invention. In this experiment, after repeatedly recording the same data signals in the sector of the optical disc, the jitter values are shown. After recording repeatedly 100,000 times, on the basis of the guideline of error probability of less than once in 10,000 times at the time of demodulation, the jitter value of 15% or less is regarded as the standard of data reproduction.

In curve 50, the maximum changing amount of the first gap field is $J_{\max}=15$ channel bits, and the maximum changing amount of the first guard data recording field is $K_{\max}=7$ bytes, and in curve 51, the maximum changing amount of the first gap field is $J_{\max}=15$ channel bits, and the maximum changing amount of the first guard data recording field is $K_{\max}=7$ bytes, and polarity inversion is included.

As can be seen from curves 50 and 51, the desired conditions can be satisfied by the maximum changing amount of the first gap field of $J_{\max}=15$ channel bits, maximum changing amount of the first guard data recording field of $K_{\max}=7$ bytes, and inclusion of polarity inversion. From the viewpoint of disc capacity, it is desired that the changing amounts of the first gap field and first guard data recording field be as small as possible, and hence it is judged that the combination of maximum changing amount of the first gap field of $J_{\max}=15$ channel bits, maximum changing amount of the first guard data recording field of $K_{\max}=7$ bytes, and polarity inversion is preferred.

In the stage of the present experiment, incidentally, the random shift was $J_{\max}=15$ channel bits and $K_{\max}=7$ bytes, but, in the future, along with the technical progress such as development of high performance recording thin film material, it is believed that the error probability rate may be lower than once in 10,000 times in

demodulation after 100,000 times of repeated recording even at a smaller shift width. In such a case, too, according to the invention, as in this embodiment, it is possible to suppress the effects of the deterioration phenomenon on the accurate recording and reproducing of information at a certain limited random shift amount.

5 Thus, according to the present embodiment, by randomly changing the length of the first gap field and first guard field in every recording, and by inverting the polarity of record signal in every recording, at the maximum changing amount of the first gap field of $J_{\max}=15$ channel bits, maximum changing amount of the first guard data recording field of $K_{\max} = 7$ bytes, signal processing is facilitated in a limited random shift amount, and effects of the two types of deterioration phenomenon in every sector and in every mark on the accurate recording and reproducing of information can be suppressed.

10 In the present embodiment, by setting the recording pattern of guard data in the first guard data recording field to the same recording pattern in the synchronous signal field, and keeping continuous the phase of the record signal between the first guard data recording field and synchronous signal interval, the synchronous signal interval is expanded, and system stability can be enhanced.

15 Moreover, in the optical disc device using the reproduced light output and at least one type or more of recorded light output, regardless of the type of the recording medium, evidently, the invention can be applied not only in the phase change optical disc, but also in magneto-optical discs and others.

20

WHAT IS CLAIMED IS:

1. An optical disc, comprising:
a plurality of sectors disposed on a track of the optical disc, each of said sectors including (i) a header field containing a sector identification signal, and (ii) a
5 data recording field containing a synchronous signal field, and
each of said sectors also including a guard data recording field, disposed between said header field and said data recording field, for recording guard data.
2. An optical disc of claim 1, wherein said synchronous signal field
contains a synchronous signal for synchronizing a starting portion of said data
10 recording field and user data is disposed adjacent the synchronous signal.
3. An optical disc of claim 1, wherein the guard data in said guard data recording field is the same as a recording pattern of the synchronous signal.
4. An optical disc of claim 3, wherein the phase of the recording pattern
is continuous near the boundary of said guard data recording field and said
15 synchronous signal field.
5. An optical disc of claim 1, wherein a recording interval of said guard data recording field is randomly changeable in every recording.
6. An optical disc of claim 5, wherein the recording interval of said guard data recording field is changeable by an amount of 7 bytes or less, and is randomly
20 changeable by a unit of 1 byte, in every recording.
7. An optical disc of claim 6, wherein the period of 1 byte is 548 ns and the frequency of a channel bit for composing 1 byte by 16 channel bits is 29.18 Mhz.
8. In an optical disc having a plurality of sectors, and having a header field containing a sector identification signal and a data recording field containing a

synchronous signal and user data in each one of said sectors, each one of said sectors, comprising: a first no-signal interval gap field, a first guard data recording field for recording guard data, said data recording field, a second guard data recording field, and a second no-signal interval gap field, the total length of said first and second gap fields being constant, the total length of said first and second guard data recording fields being constant, the length of said first gap field and said first guard data recording field being randomly changeable in every recording, and the changing amount of said first gap field being smaller than the changing amount of said first guard data recording field.

10 9. An optical disc of claim 8, wherein the resolution of the changing amount of said first gap field is a channel bit unit, and the resolution of the changing amount of said first guard data recording field is a byte unit.

10. An optical disc of claim 8, wherein the polarity of the guard data and signal in the data recording field is randomly changeable in every recording.

15 11. An optical disc of claim 9, wherein the resolution of the changing amount of said first gap field is 15 channel bits or less, and the resolution of the changing amount of said first guard data recording field is 7 bytes or less.

20 12. An optical disc of claim 8, wherein the guard data in said first and second guard data recording fields is the same as the recording pattern of the synchronous signal.

25 13. An optical disc device, operative on an optical disc having a plurality of sectors divided from a track, each of said sectors having a header field containing a sector identification signal and a data recording field containing a synchronous signal field, the optical disc device, comprising:

guard data generating means for generating guard data; and

first record controlling means for recording the guard data in a guard data recording field disposed between said header field and said data recording field.

14. An optical disc device of claim 13, wherein said synchronous signal field includes a synchronous signal for synchronizing a starting portion of said data recording field and user data is disposed adjacent the synchronous signal.

15. An optical disc device of claim 13, wherein the guard data in said guard data recording field is the same as a recording pattern of the synchronous signal.

16. An optical disc device of claim 15, wherein the phase of the recording pattern is continuous near the boundary of said guard data recording field and said synchronous signal field.

17. An optical disc device of claim 13, further comprising first random changing means for randomly changing the recording interval of said guard data recording field.

18. An optical disc device of claim 17, wherein said random changing means randomly changes a changing amount of 7 bytes or less of the guard data recording field in every recording with a resolution unit of 1 byte.

19. An optical disc device of claim 18, wherein the period of 1 byte is 548 ns and the frequency of a channel bit for composing 1 byte by 16 channel bits is 29.18 MHz.

20. An optical disc device, operative on an optical disc having a plurality of sectors divided from a track, each of said sectors having a header field containing a sector identification signal and a data recording field containing a synchronous signal and user data, the optical disc device, comprising:

guard data generating means for generating guard data in first and second guard data recording fields;

random changing means for (i) randomly changing the length of first and second gap fields, the total length of said first and second gap fields being constant, and (ii) randomly changing the length of first and second guard data recording fields, the total length of said first and second guard data recording fields being constant; and

record controlling means for recording signals in said first and second guard data recording fields and said data recording field, on the basis of the changing amount of said first and second gap fields and the changing amount of said first and second guard data recording fields.

21. An optical disc device of claim 20, wherein the resolution of the changing amount of said first and second gap fields is in the unit of channel bits, and the resolution of the changing amount of the first and second guard data recording fields is in the unit of bytes.

22. An optical disc device of claim 20, further comprising polarity changing means for randomly changing the polarity of the guard data and signals in the data recording field in every recording.

23. An optical disc device of claim 21, wherein the random changing means changes said first gap field by an amount of 15 channel bits or less in every recording, and changes said first guard data recording field by an amount of 7 bytes or less.

24. An optical disc device of claim 20, wherein the guard data in said first and second guard data recording fields is the same as the recording pattern of the synchronous signal.

25. A recording method, comprising the steps of: providing an optical disc having a plurality of sectors divided from a track, each of said sectors having a header field containing a sector identification signal and a data recording field containing a synchronous signal field; and

5 recording guard data in a guard data recording field disposed between said header field and said data recording field.

26. A recording method for an optical disc of claim 25, further comprising providing said synchronous signal field with a synchronous signal for synchronizing a starting portion of said data recording field and providing user data adjacent the
10 synchronous signal.

27. A recording method for an optical disc of claim 26, further comprising providing guard data in said guard data recording field that is the same as the recording pattern of the synchronous signal.

28. A recording method for an optical disc of claim 27, further comprising
15 setting the phase of the recording pattern to be continuous near the boundary of said guard data recording field and said synchronous signal field.

29. A recording method for an optical disc of claim 25, further comprising randomly changing in every recording the recording interval of said guard data recording field.

20 30. A recording method for an optical disc of claim 29, further comprising setting the changing amount of the recording interval of said guard data recording field to 7 bytes or less, and randomly changing the amount in every recording by a unit of 1 byte.

25 31. A recording method for an optical disc of claim 30, further comprising setting the period of 1 byte to 548 ns and the frequency of a channel bit for composing 1 byte by 16 channel bits to 29.18 MHz.

32. A recording method for an optical disc having a plurality of sectors divided from a track, each of said sectors having a header field containing a sector identification signal and a data recording field containing a synchronous signal and user data, the method comprising the steps of:

5 sequentially forming a sector structure comprised of a first no-signal interval gap field, a first guard data recording field for recording guard data, said data recording field, a second guard data recording field, and a no-signal interval second gap field;

10 setting the total length of said first and second gap fields constant, setting the total length of said first and second guard data recording fields constant, and when recording, randomly changing the length of said first gap field and said first guard data recording field in every recording and

controlling the change amount of said first gap field to be smaller than the changing amount of said first guard data recording field.

15 33. A recording method for an optical disc of claim 32, further comprising setting the changing amount of said first gap field to a resolution unit of channel bits, and setting the changing amount of said first guard data recording field to a resolution unit of bytes.


20 34. A recording method for an optical disc of claim 32, further comprising randomly changing in every recording the polarity of the guard data and signals in said data recording field.

35. A recording method for an optical disc of claim 33, further comprising setting the changing amount of said first gap field to 15 channel bits or less, and setting the changing amount of said first guard data recording field to 7 bytes or less.

25 36. A recording method for an optical disc of claim 32, further comprising setting the guard data in said first and second guard data recording fields to be the same as the recording pattern of the synchronous signal.

1/19

FIG. 1






FIG. 2a Initial 1 time of repetition




FIG. 2b 50,000 times of repetition




FIG. 2c 100,000 times of repetition

FIG. 3




FIG. 4a




FIG. 4b

Period
interval by
1 time of
repetition




FIG. 4c

100,000
times of
repetition





FIG. 4d

Period
interval by
100,000
times of
repetition



5/19

FIG. 5a


Initial
time of
repetition

FIG. 5b


Period
interval
by 1 time
of
repetition

FIG. 5c



100,000
times of
repetition

FIG. 5d

Period
interval
by 100,000
times of
repetition





FIG. 7






FIG. 8a Sector 1




FIG. 8b Sector 2




FIG. 8c Sector 3






FIG. 8d Sector 4

FIG. 9




10/19

FIG. 10



11/19

FIG. 11



12/19

FIG. 12






FIG. 13










FIG. 16a




FIG. 16b



Record state

FIG. 16c



17/19

FIG. 17






FIG. 18



19/19

FIG. 19



INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP 97/03559

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G11B7/013 G11B7/00 G11B20/12 G11B27/19 G11B27/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 718 831 A (MATSUSHITA ELECTRIC IND CO LTD) 26 June 1996	1-5, 8, 10, 12-17, 20, 22, 24-29, 32, 34, 36
A	see abstract see page 1, line 54 - page 2, line 33 see page 9, line 32 - page 10, line 53; figure 21	6, 7, 9, 11, 18, 19, 21, 23, 30, 31, 33, 35
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

23 February 1998

Date of mailing of the international search report

05/03/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Annibal, P

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/JP 97/03559

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 674 314 A (TOKYO SHIBAURA ELECTRIC CO) 27 September 1995 see column 1, line 1 - column 2, line 40 see column 5, line 55 - column 7, line 37; figure 1	1,2,13, 14,25,26
A		3-9,12, 15-21, 24, 27-34,36
A	----- PATENT ABSTRACTS OF JAPAN vol. 018, no. 042 (P-1680), 21 January 1994 & JP 05 266490 A (FUJI ELECTRIC CO. LTD), 15 October 1993, see abstract	
E	----- EP 0 814 463 A (MATSUSHITA ELECTRIC IND CO LTD) 29 December 1997 see page 1, line 34 - line 41 see page 6, line 42 - page 7, line 18; figures 7,8 -----	1-5,8, 10, 12-17, 20,22, 24-29, 32,34,36

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 97/03559

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0718831 A	26-06-96	JP 8180410 A JP 9219022 A	12-07-96 19-08-97
EP 0674314 A	27-09-95	JP 7262566 A US 5604727 A	13-10-95 18-02-97
EP 0814463 A	29-12-97	JP 9320054 A	12-12-97